

# Mobil Antifreeze

## Description

- Concentrated antifreeze formula.
- Contains Mono Ethylene Glycol. Helps to prevent winter freezing and summer overheating.
- Three years protection
- Meets exacting quality standard BS6580-1992.
- Mobil Antifreeze should not be mixed with silicate free, OAT engine coolants.



## Product Directions

Mobil Antifreeze must be diluted with water before use. It is hard water compatible and can be mixed with tap water before filling into the cooling system.

### Dilution chart

Antifreeze	Water	Freeze protection
12%	88%	-5°C
25%	75%	-12°C
33%	67%	-18°C
50%	50%	-38°C
60%	40%	-62°C

For preparation of the coolant use clean, not overly hard water. Waste from mining, sea water, brackish water, brine, industrial waste water are all unsuitable.

Water hardness	0 to 20 °dGH (0 - 3.6 mmol/l)
Chloride content	max. 100 ppm
Sulphate content	max. 100 ppm

## Technical Specifications

Colour	blue
Density at 20 °C	1.13 g/cm <sup>3</sup>
Boiling point	≥ 165 °C
Flash point	> 115 °C
pH value	7.7
Reserve alkalinity: M/10 HCl	21 ml
Water content	max. 5 %

### Pack sizes :

- 1l, 5l, 20l & 208l

